

TOUGH IMPACT GUNS FOR TOUGH JOBS

Impact Wrenches 3/8" Sq. Drive

215



- Compact 3/8" Drive
- Heavy Duty
- Max Torque: 160 ft-lb
- Adjustable Power
- Handle exhaust

216



- Palm Grip 3/8" Drive
- Super Duty
- Max Torque: 175 ft-lb
- Butterfly fwd/rev action
- Recessed regulator dial
- Handle exhaust

2115Ti *Lightweight Composite Body*



- Ultimate Compact 3/8" Drive
- Ultra Duty
- Max Torque: 280 ft-lb
- Adjustable Dial Power
- Handle exhaust

TITANIUM

Impact Wrenches 1/2" Sq. Drive

235



- 1/2" Drive
- Heavy Duty
- Max Torque: 375 ft-lb
- Adjustable Power
- Handle exhaust

2125PTi *Lightweight Composite Body*



- Ultimate Compact 1/2" Drive
- Ultra Duty
- Max Torque: 280 ft-lb
- Adjustable Dial Power
- Handle exhaust
- Super Quiet 2125PQT Available

TITANIUM

131S



131S-2

- Super Duty
- Max Torque: 425 ft-lb
- Pressure feed lubrication
- Adjustable power regulator
- Handle exhaust
- 131S-2" ext. anvil avail.

231C



- Super Duty
- Max Torque: 600 ft-lb(rev)
- Pressure feed lubrication
- Adjustable power regulator
- Front exhaust



2130AP

NEW



- Heavy Duty 1/2" Drive
- Max Torque: 600 ft-lb
- Adjustable Dial Power
- Handle exhaust
- 2" extended anvil model avail.

TITANIUM

2131A

2131A-2



- Ultra Duty 1/2" Drive
- Max Torque: 600 ft-lb
- Adjustable Dial Power
- Handle exhaust
- 2" extended anvil model avail.

Lightweight Composite Body

2135Ti

Up to 1000 ft-lb nut busting torque!



- Ultimate 1/2" Drive
- Ultra Duty
- Max Torque: 700 ft-lb
- Adjustable Dial Power
- Handle exhaust
- Super Quiet 2135QTI Available

TITANIUM

Impact Wrenches 3/4" Sq. Drive

252



- Standard Duty 3/4" Drive
- Max Torque: 750 ft-lb
- Adjustable Dial Power
- Handle exhaust
- Great general maintenance tool

258

258-3



- Heavy Duty 3/4" Drive
- Max Torque: 1000 ft-lb
- Adjustable Dial Power
- Handle exhaust
- Ideal for trucks and heavy equipment repairs
- 3" extended anvil model avail. (258-3)


2141



- Ultra Duty 3/4" Drive
- Max Torque: 1200 ft-lb
- Weighs just 3.2kg
- Handle exhaust
- Only 208mm long


Lightweight Composite Body

Only three moving parts.



SingleHammer

Excellent power-to-weight ratio.



TwinHammer

261

261-3

261-6



- Super Duty 3/4" Drive
- Max Torque: 1100 ft-lb
- Jumbo Hammer Power
- Adjustable Power
- Handle exhaust
- Pressure Feed Lubrication
- Available with standard, 3" or 6" ext. Anvil

2925P1Ti



- Ultra Duty 3/4" Drive
- Max Torque: 1450 ft-lb
- Twin Hammer Power
- Adjustable Dial Power
- Handle exhaust
- Corrosion protection

TITANIUM

2925RBP1Ti

Reverse Bias



- Ultra Duty 3/4" Drive
- Max Torque: 1600 ft-lb
- Twin Hammer Power
- Adjustable Dial Power
- Handle exhaust
- Corrosion protection

TITANIUM

Integrity Pumps & Engineering

"A new standard in pump, engineering and pneumatic supplies & service"

2 Second Ave Unanderra 2526
Tel: +6 1 2 4271 2733
Fax: +6 1 2 4271 4834

Distributor of:

IR Ingersoll-Rand

Professional Tools

Model	Drive	Impacts		Maximum torque		Recommended torque range		Weight	Length	Hose Connection	Size hose recommended	
		Free speed	per minute	Nm	ft-lb	Nm	ft-lb				in	in
215	3/8"	9500	1600	217	160	20-176	15-129	1.3	156`	1/4"	3/8"	10
216	3/8"	9500	1600	232	175	20- 217	15-160	1.3	156`	1/4"	3/8"	10
2115Ti	3/8"	15000	1500	379rev	280rev	34- 312	25-230	1.1	142`	1/4"	3/8"	10
225	1/2"	7500	1200	441	325	34- 272	25-200	1.9	168	1/4"	3/8"	10
2125Ti	1/2"	15000	1500	379rev	280rev	34- 312	25-230	1.1	142`	1/4"	3/8"	10
235	1/2"	9500	1200	510	375	34- 306	25-225	2.5	197	1/4"	3/8"	10
131S	1/2"	8000	1200	575	425	34- 407	25-300	2.6	185	1/4"	3/8"	10
231C	1/2"	8000	1200	816	600rev	34- 407	25-300	2.6	185	1/4"	3/8"	10
2130AP	1/2"	9500	1200	814	600	34- 474	25- 350fwd	1.9	184	1/4"	3/8"	10
						745 rev.	500 rev.					
2131A	1/2"	9500	1250		600	68- 544	50-400	2.0	180	1/4"	3/8"	10
2135Ti	1/2"	9500	1250	949rev.	700rev.	68- 814	50-600	1.79	186	1/4"	3/8"	10
				848fwd.	625fwd	68- 814	50-600					
252	3/4"	6500	1200	1020	750	136-680	100-500	3.9	229	3/8"	1/2"	13
258	3/4"	6200	1100	1360	1000	272-1080	200-800	4.89	249	3/8"	1/2"	13
261	3/4"	5500	1100	1496	1100	272-1224	200-900	5.3	203	3/8"	1/2"	13
2141	3/4"	7250	1175	1627	1200	271-1220	200-900	3.2	208	3/8"	1/2"	13

Impact Wrenches 1" Sq. Drive
271



- Super Duty 1" Drive
- Max Torque: 1100 ft-lb
- Jumbo Hammer Power
- Adjustable Power
- Handle exhaust
- Pressure Feed Lubrication

2925P3Ti



- Super Duty
- 1" Drive
- Max Torque: 1450ft-lb
- Twin Hammer Power
- 4 Position Power Dial
- Handle exhaust
- Corrosion protection

New Model!

TITANIUM

2190Ti-6



- Ultra Duty
- 1" Drive
- Max Torque: 1650ft-lb
- Twin Hammer Power
- 7 vane motor
- 4 Position Power Dial

The 2190Ti-6 allows user to operate tool in a more comfortable position

New Model!

TITANIUM

295



Perfect for truck repairs & Construction Work

- Heavy Duty 1" Drive
- Max Torque: 1,450 ft-lb
- Top mount handle
- 3 position power regulator
- Handle exhaust

285A Perfect for truck repairs & Construction Work



- Heavy Duty 1" Drive
- Max Torque: 1,450 ft-lb
- Side handle
- 3 position power regulator
- angled down exhaust
- 360 degree swivel inlet

285A-6

**Compare apples with apples
This range is equivalent to the heaviest duty available from most other air tool manufacturers!**



2190Ti



- Ultra Duty
- 1" Drive
- Max Torque: 1650ft-lb
- Twin Hammer Power
- Tyre change - "ergonomic handle"
- 7 vane motor
- 4 Position Power Dial

New Model!

TITANIUM

2190DTi-6



- Ultra Duty
- 1" Drive
- Max Torque: 1650ft-lb
- Twin Hammer Power
- 7 vane motor
- 4 Position Power Dial

New Model!

TITANIUM

2925B2Ti



- Super Duty
- 1" Drive
- Max Torque: 1650ft-lb
- Twin Hammer Power
- 7 vane motor
- 4 Position Power Dial
- Corrosion protection

New Model!

TITANIUM

2934B2



- Super Duty
- 1" drive
- Max Torque: 1500ft-lb
- Twin Hammer
- Pressure feed lubrication
- Powerful IR Industrial grade tool
- Optional 90 degree angle drive available

2940B2



- Super Duty
- 1" drive
- Max Torque: 2000ft-lb
- Twin Hammer
- Pressure feed lubrication
- Powerful IR Industrial grade tool
- For the toughest 1" drive applications

2950B7



- Super Duty
- 1 1/2" drive
- Max Torque: 3000ft-lb
- Twin Hammer
- Pressure feed lubrication
- Powerful IR Industrial grade tool
- The Ultimate in long life IR power

Integrity Pumps & Engineering
"A new standard in pump, engineering and pneumatic supplies & service"

2 Second Ave Unanderra 2526
Tel: +6 1 2 4271 2733
Fax: +6 1 2 4271 4834

Distributor of:
IR Ingersoll Rand
Professional Tools

Model	Drive	Impacts		Maximum torque		Recommended torque range		Weight	Length	Hose Connection	Size hose recommended	
		Free speed	per minute	Nm	ft-lb	Nm	ft-lb				in	in
Pistol Grip												
2925P1Ti	3/4"	5200	1050	1972	1450	476-1496	350-1100	5.4	225	3/8"	1/2"	13
2925RBP1Ti	3/4"	5200	1050	2176	1600rev	1904	1400rev	5.4	225	3/8"	1/2"	13
				1768	1300fwd	408-1292	300-950fwd					
271	1	5500	1200	1496	1100	136-1020	100-750	5.67	178	3/8"	1/2"	13
295	1	5000	750	1972	1450	136-1360	100-1000	9.98	267	3/8"	1/2"	13
2925P3Ti	1	5200	1050	1972	1450	476-1496	350-1100	5.6	225	3/8"	1/2"	13
Chainsaw Grip												
2190Ti	1	6800	875	2238	1650	204-1627	150-1200	6.1	391	3/8"	1/2"	13
2190Ti-6	1	6800	875	2238	1650	204-1627	150-1200	7.0	546	3/8"	1/2"	13
D-Handle												
2190DTi-6	1	6800	875	2238	1650	204-1627	150-1200	7.0	474	3/8"	1/2"	13
2925B2Ti	1	6500	900	2170	1650	475-1904	350-1400	6.4	314	3/8"	1/2"	13
285	1	5000	750	1972	1450	136-1360	100-1000	10	335	1/2"	3/4"	19
285-6	1	5000	750	1972	1450	136-1360	100-1000	11.4	511	1/2"	3/4"	19
2934B2	1	6600	750	2030	1500	678-1490	500-1100	8.39	286	1/2"	3/4"	19
2940B2	1	5000	850	2710	2000	1360-2170	1000-1600	10.0	311	1/2"	3/4"	19
2950B7	1 1/2"	3750	650	4080	3000	2170-3390	1600-2500	14.8	368	1/2"	3/4"	19