

CE

GROUT PUMP P100

Quality System
Quality
Endorsed
Company
ISO 9001:2000
Lic No. QEC 21300
Standards Australia



This lightweight Mixer is used to mix grout or Tekflex

One main air connection

Mixer is fitted with an in-line lubricator which supplies both motors

A separate air take off, fitted with 1/2" BSP ball valve, is in-line before lubricator. This can be used for spray nozzles

Can supply outlets on pump to suit any application

Mixer Motor is variable speed from 0 - 275 RPM with a ball valve for quick shut down

Mixer Motor and mixing blade can be quickly removed from top of drum.

Drive shaft, mixing blade and deflector plates are all stainless steel

Drum can be separated from pump and base for ease of cleaning

The unit can be broken up into 4 separate sections:

- Pump Frame & Motor
- Tank & Frame
- Mixer Motor & Mounting Bracket
- Air Inlet Assembly



Manufactured by:
RAMBOR PTY LTD
ABN 61 105 301 184
2 Second Ave Unanderra 2526
Tel: +6 1 2 4271 2733
Fax: +6 1 2 4271 4834



Integrity Pumps & Engineering
"A new standard in pump, engineering and pneumatic supplies & service"



Optional extra

The Rambor Water Separator is a lightweight design with a transparent water chamber, enabling the operator to visually check for water in the system and drain when present



Pump

Pump Rate	up to 17 l/min
Delivery Pressure	16 Bar
Pumping Distance pressure	20 metres at 4 metres head
Pump Inlet	100 mm

Technical Specifications

Weight	115 kg (fully assembled)
Dimensions	length 1410mm x height 1000mm x width 540mm
Tank Capacity	100 litres

	<u>Pump Motor</u>	<u>Mixer Motor</u>
Part Number	RTMM924	DRM30-243
Model	95mm 14:39 ratio	30mm 11:42 ratio 14:39 ratio
Free Rotation Speed	0 - 850 rpm variable	0 - 275 rpm variable
Stall Torque	251 Nm / 185 ft/lbs	330 Nm / 243 ft/lbs
Air Consumption	120 cfm / 3115 l/min	90 cfm / 2549 l/min
Operating Pressure	7 Bar	7 Bar
Minimum Supply Hose	25mm	25mm